

DATA SHEET 20789.310.38900

## Folajet QD-CLSC

A top coated clear static cling film for high resolution photographic posters, mock ups, signage, decals, point of sale displays, signs and labels. A soft back layer clings without any adhesive to clean smooth surfaces like glass, plexi-glass, polished metal or furniture. This film can be repositioned without leaving any adhesive residue. It gives excellent flatness and colour contrast reproduction even when using high levels of ink, reducing the possibility of material distortion. The film offers excellent handling, tough dimensional stability and is tear resistant. Images dry quickly.

### Printing Systems



### Rolls

Art.Number	Nominal thickness (mm)	Width (mm)	Length (m)
20789.310.38900	0.310	914	15

### Technical data

#### Characteristic

- Suitable for dye inks
- Suitable for piezo Ink Jet printer
- Suitable for thermal Ink Jet printer
- Good flatness
- Clings to smooth surfaces like glass, plexi etc.
- High resolution
- Can be repositioned without permanently bonding to surfaces
- No bleeding
- Tear resistant
- Fast dry

## Finish

- Clear transparent

## Specifications

Nominal thickness (mil)	12.4
Nominal thickness (mm)	0.310
Coating Printsides	Ink Jet
Width (inch)	36
Width (mm)	914
Printside	Glossy side
Length (ft)	49.22
Length (m)	15
Backside	Release liner
Base Material	Polyester film
Packing quantity	1

## Compatibility

### Handling

- Between 15-30°C and 30-70% r.h.
- A preconditioning period of 24 hours within the printing environment is recommended.
- Avoid fingerprints on printing side.

### Storage

- Shelf life 1 year after delivery (under above storage conditions)
- Store in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

### Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.

