

DATA SHEET 22157.310.30400

SI 157

Ink Jet Canvas for framed printings or for stretching on wooden frames. Material 30 / 70% polyester / cotton, coated on one side, with natural structured surface. Suitable for art prints, lifestyle posters, exhibition work and stage decoration.

Printing Systems			
UYE LATEK PIGMENT			
Rolls			
Art.Number	Width (mm)	Grammage	Length (m)
Art.Number 22157.310.35800	Width (mm) 610	Grammage 310 g/m ²	Length (m) 15
22157.310.35800	610	310 g/m²	15
22157.310.35800 22157.310.38900	610 914	310 g/m ² 310 g/m ²	15 15

Technical data

Characteristic

- High brillance of colours
- Flexible coating for good strechability
- Natural finish on the reverse side
- Low-reflective printing surface
- Tear resistant

Finish

• Natural, matt





Specifications

Coating Printside	microporous coating	
Width (mm)	1067	
Grammage	310 g/m²	
Core Diameter	76 mm	
Length (m)	15	
Base Material	Polycotton (70% cotton, 30% polyester),	
	1:1 weave	
Packing quantity	1 roll	

Compatibility

· Suitable for most large format Ink Jet printers using waterbased dye, pigment or latex inks

Handling

- An additional protection of the printed surface is required when it is subject to abrasion, hand perspiration or other mechanical influences. In this case the print must be protected with a suitable clear varnish or a liquid lamination product.
- When using dye inks, the printed image must be protected in any case with a clear varnish or a liquid lamination product in order to improve the colour fastness.

Storage

- Shelf life: 1 year after delivery
- Store in a cool and dry place at a room temperature of 15 25°C and at a humidity of 30 60%.

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.