

22VN0.100.35000



|                 |      |          |    |
|-----------------|------|----------|----|
| 22VN0.100.34000 | 430  | 0.130 mm | 20 |
| 22VN0.100.35900 | 610  | 0.130 mm | 20 |
| 22VN0.100.39000 | 914  | 0.130 mm | 20 |
| 22VN0.100.30500 | 1067 | 0.130 mm | 20 |
| 22VN0.100.32000 | 1270 | 0.130 mm | 20 |
| 22VN0.100.33300 | 1370 | 0.130 mm | 20 |
| 22VN0.100.35000 | 1520 | 0.130 mm | 20 |

- 
- 
- 
- 

- 
-



|  |                                                                 |
|--|-----------------------------------------------------------------|
|  | Silikonpapier ~ 0.145 mm                                        |
|  | Nanoporöse Beschichtung                                         |
|  | 1520                                                            |
|  | 0.130 mm                                                        |
|  | 76 mm                                                           |
|  | frisch $\geq 3.5$ N, nach 24 Std. $\geq 10$ N                   |
|  | Polyacrylat Dispersion                                          |
|  | 20                                                              |
|  | Kalandrierte Weich-PVC-Folie, monomer<br>weichgemacht, 0.100 mm |
|  | 0.285 mm                                                        |
|  | 1 Rolle                                                         |

•

•

•

•

•

•

•