

DATA SHEET 22PMP.060.09110

Label Jet PP Matt White P

White matt self-adhesive PP film with paper backing, permanent adhesive. Ideal for stickers, signs and decals.

Printing Systems



Rolls

| Art.Number | Width (mm) | Thickness | Length (m) |
|-----------------|------------|-----------|------------|
| 22PMP.060.09110 | 1070 | 0.060 mm | bulk roll |

Technical data

Characteristic

- High brilliance of colours
- Good wet smear resistance
- High Level Ink Absorption
- Inkjet coating for the indirect food contact ISEGA / FDA-certified
- Permanent self adhesive
- Low-reflective printing surface
- Tear resistant
- Very fast ink drying
- Universal use

Finish

- self-adhesive with paper backing
- White matt

Specifications

| | |
|--------------------------------|---|
| Release liner | siliconized paper |
| Coating Printsides | microporous coating |
| Width (mm) | 1070 |
| Thickness of carrier material | 0.060 mm |
| Adhesion strength | >/= 3.5 N, after 24 h >/= 5.0 N (AA02 based on FINAT FTM1) |
| Type of adhesive | acrylate dispersion, permanent |
| Length (m) | bulk roll |
| Roll width / Roll usable width | Please contact Folex if you need other roll widths and roll lengths. We can convert the rolls according to your wishes. |
| Base Material | Polypropylene |
| Total thickness | 0.170 mm |

Compatibility

Handling

- Gluing:

All even, smooth surfaces which are dry and free of dirt, grease, silicon etc. can be adhered. The surface to be glued must be checked for suitability before adhesion and properly prepared (cleaned). It is up to the user to test for their own suitability/application, due to the wide variety of surfaces, applications & desired results.

Gluing temperature at least 5° C

Service temperature min -20°C, max +80°C

- Durability:

The durability of the glued label is heavily influenced by the prevailing ambient conditions, the place of use and the bases!

Storage

- Shelf life: 1 year after delivery
- In its original packing at 20-25°C, 45-55% humidity.

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.